



### DASH Enclosure Specifications

Measurements: 5' w x 39" d x 68" h

- ❖ 10 gauge steel construction
- ❖ 1" insulation throughout interior
- ❖ 3/4" radius corners on the front
- ❖ 10-degree roof slope, front to back
- ❖ 2 weather tight doors on rear with 2 recessed key locks, protected with non-drillable hard plate and high security hinges welded to frame and door.
- ❖ 2- 20Amp circuits
 

Circuit 1	AC & lighting
Circuit 2	ATM
- ❖ 4' fluorescent lighting
- ❖ Internal air conditioning unit
- ❖ Optional heater available
- ❖ Two tone color standard
- ❖ Two – four coats of high quality Automotive Acrylic Enamel. Est. weight 1200 lb.

### DASH Security Features

- Cutting the enclosure door hinges will not open the doors. DASH utilizes a locker bar on each door that precludes access by a perpetrator even with the hinges removed, they can not gain access.
- Recessed non drillable locks, lock areas are protected with high manganese work- hardening armor. (The more they drill the harder the metal becomes.) The manganese plate is welded to our proprietary machined locking assembly which will not allow a drill bit to penetrate.
- Steel seams are welded inside and out, which means that the enclosure will not collapse inward if a chain is wrapped around it, thus not exposing the ATM.
- Adds added security for business hour and level one type ATM safes.
- Optional lighted canopy increases customer awareness and brand recognition.
- The unique DASH sealed weather proof lighting fixture is spring loaded allowing it to spring up and back into location, minimizing vandalism.

Call for a distributor in your area.  
 918-296-9061  
[info@dashatm.com](mailto:info@dashatm.com)  
 dashatm.com

The DASH enclosure can be manufactured to accommodate any "Through-The-Wall" ATM currently on the market.

Copyright © 2003- 2005 DASH ATM